



**EATON**

## Synflex HCR Collapse Proof Hose


Product Details



### Applications

- Hydraulic Flying Leads
- Workover Umbilical Component
- Hot Lines
- Chemical and Water Injection

## Engineered for High Pressure and Low Volumetric Expansion



Synflex® Subsea HCR Collapse Proof Hoses are reinforced with aramid (Kevlar®) fiber bonded to the core tube and cover. The tube is a smooth, seamless, continuous extrusion of Besno Nylon 11 P40TLO, and the flexible 316 stainless

steel interlocking metal carcass is capable of withstanding over 5,000 psi differential pressure.

### Features

- Available in 5,000 psi and 7,500 psi working pressure with a 4:1 safety factor
- API 17E, ExxonMobile GP 65-05-06, GP 65-05-03 compliant
- Reinforced with aramid (Kevlar) fiber
- Seamless core tube extruded from Besno Nylon 11 P40TLO
- Flexible 316 stainless steel innerlocking carcass withstands over 5,000 psi differential pressure
- Chemical, abrasion and UV resistant nylon outer cover

### Benefits

- The ultimate problem-solving hose for deep sea applications
- Superior life expectancy in the most demanding applications
- Multiple sizes to meet many needs
- Rugged and dependable, designed to withstand the most demanding applications and environments
- Available in very long continuous lengths for subsea applications



**Synflex Subsea HCR Collapse Proof Hose**

Standard Compliance

- API 17E
- GP 65-06-03
- GP 65-05-06

- Available in long continuous lengths over 10,000' long
- Available in single length or bundle component

- 316 stainless steel fittings with a wide array of hose ends

#	NOMINAL I.D.		MAXIMUM O.D.		MAX. WORKING PRESSURE AT AMBIENT TEMP.		MIN. BURST PRESSURE		MIN. BEND RADIUS		WEIGHT		FITTING
	in	mm	in	mm	psi	bar	psi	bar	in	mm	100ft	100m	
33CP-08	1/2	12.7	1.085	27.6	5,000	345	20,000	1,379	18.0	457	43.3	64.40	9C408
33CP-16	1	25.4	1.740	44.2	5,000	345	20,000	1,379	20.0	508	112.0	166.60	9C416
35CP-08	1/2	12.7	1.185	30.1	7,500	517	30,000	2,068	18.0	457	47.0	69.9	9C408

**Eaton**  
 Hydraulics Operations USA  
 14615 Lone Oak Road  
 Eden Prairie, MN 55344  
 USA  
 Tel: 952 937-9800  
 Fax: 952 974-7722  
 www.eaton.com/hydraulics

**Eaton**  
 Hydraulics Operations USA  
 115 Lena Dr.  
 Aurora, OH 44202  
 USA  
 Tel: 330 274-3171  
 Toll Free: 800 837-1467  
 Fax: 330 274-0473

**Eaton**  
 Hydraulics Operations Europe  
 Gembloux S.A./N.V.  
 Chaussee de Tirlemont, 100  
 B-5030 Gembloux  
 Belgium  
 Tel: (32) 81-626-211  
 Fax: (32) 81-615-789

